Beaumont Fire-Rescue Services

PERFORMANCE BENCHMARKS

402.10I

Two-Firefighter Connection of the 5" Storz to 2-1/2" Wye Appliance
To a Standpipe/Sprinkler FDC

Discipline: Fire Protection Systems

Effective: 3/5/2011

Revised:
Replaces:

Anne Huff, Fire Chief

I. Objective

The firefighter, using two 25' sections of $2^{-1}/2$ " fire hose, 100' of 5" hose and the 5" Storz to $2^{-1}/2$ " wye appliance, shall demonstrate the proper procedure for a two-firefighter connection method to the standpipe/sprinkler FDC. The firefighters shall be given a maximum of three (3) minutes to complete the skill.

II. <u>Instructions – Procedures for Achieving the Objective</u>

While wearing full protective clothing and a self-contained breathing apparatus (SCBA), you shall demonstrate the two-firefighter method of connecting the 5" Storz to 2-½" wye adaptor and 5" hose from the apparatus to the standpipe/sprinkler FDC. You will have a maximum time limit to complete this skill of three (3) minutes. You will begin on my instruction to start. The skill will end when you state to me that you have completed the identified steps. Do you understand these instructions?

III. Examiner's Note

The firefighters will not be allowed to review the performance steps at the time of testing.

IV. Preparation & Equipment

- A. Two 25' sections of $2-\frac{1}{2}$ " hose
- B. 5" Storz to $2-\frac{1}{2}$ " wye appliance
- C. Assorted spanners/wrenches to complete the task
- D. 100' of 5" hose

<u>Note</u>: The firefighters shall accomplish the skill wearing "FULL PROTECTIVE CLOTHING FOR STRUCTURAL FIREFIGHTER" as required by the <u>Texas Commission on Fire Protection</u> to include helmet, coat, boots, hood, and trousers. Gloves shall be optional. Firefighters will not don face piece or hood.

V. Reference Sources

- A. National Fire Protection Association (NFPA) 1001, 3-3.13(a)
- B. IFSTA, Essentials of Fire Fighting, 4th Edition, pages 578-584.

402.10I – Two firefighter Connection of the Storz to 2-1/2"Wye Appliance to the Standpipe/Sprinkler FDC Discipline: Fire Protection Systems

Name:				Officer #:			
Evaluator:					Officer #:		
Date:					Location:		
<u>Fir</u>	the f b) Rem 2-1/2 c) Carr 25' d) Unro e) Inspe f) Con	oins the ned oves the Star oves the Star oves the second to FD olds the 2-1/2 ects the PD nects the 2	orz to 2-½ n the appo tions of 2 C 2" sections C connect	2" wye ada aratus com -½" hose t s of hose to tions for de to the FDC	ptor and t partment . oward the oward the l bris prior	he two sections of FDC stopping	
Name:					Officer #:		
Evaluator:					Officer #:		
Date:					Location:		
<u>Fire</u>	alrea b) Conn c) Conn d) Chec	es Storz 5" dy connect nects the 5" ects the two ks to ensur	ed to FDC hose to the 2-½" ho e the wye	ne Storz to se couplin valves are	2-½" wye gs to the w in the ope	(No par ne 2-½" hose vyevye en positiond time	P/F P/F 1.0
	Points Possible	Passing Score	Attempt	Performan (Poi	_	PASS	FAIL
	7	5	First Second				